

Door Key Compatible (Key in Knob) Padlocks

Series 88 - Model Comparison

	Shackle Measurements			Body Width	
Model	Α	В	С	D	Shackle Material
88T5*	7.94mm	19.05mm	20.64mm	50.8mm	HARDENED
8811	7.94mm	28.58mm	20.64mm	50.8mm	STAINLESS STEEL BRASS
8812	7.94mm	28.58mm	20.64mm	50.8mm	HARDENED STEEL
8813	7.94mm	28.58mm	20.64mm	50.8mm	STAINLESS STEEL
8815*	7.94mm	28.58mm	20.64mm	50.8mm	HARDENED
88X3	7.94mm	38.1mm	20.64mm	50.8mm	STAINLESS STEEL STAINLESS STEEL
88X5*	7.94mm	38.1mm	20.64mm	50.8mm	HARDENED
8821	7.94mm	50.8mm	20.64mm	50.8mm	STAINLESS STEEL BRASS
8822	7.94mm	50.8mm	20.64mm	50.8mm	HARDENED STEEL
8823	7.94mm	50.8mm	20.64mm	50.8mm	STAINLESS STEEL
8825*	7.94mm	50.8mm	20.64mm	50.8mm	HARDENED STAINLESS STEEL
8831	7.94mm	76.2mm	20.64mm	50.8mm	BRASS
8832	7.94mm	76.2mm	20.64mm	50.8mm	HARDENED STEEL
8833	7.94mm	76.2mm	20.64mm	50.8mm	STAINLESS STEEL
8842	7.94mm	101.6mm	20.64mm	50.8mm	HARDENED STEEL

^{*} Meets or exceeds grade 5 of the ASTM F883 standards for cutting. Key-retaining feature available for all models in this section.

Wilson Bohannan Lock Company

621 Buckeye Street • Marion, OH 43302 • www.padlocks.com T: 800-382-3639 • F: 740-383-1653 • wbco@padlocks.com