



Door Key Compatible (Key in Knob) Padlocks

Series 88 - Model Comparison

Model	Shackle Measurements			Body Width	Shackle Material
	A	B	C	D	
88T5*	5/16"	3/4"	27/32"	2"	HARDENED STAINLESS STEEL BRASS
8811	5/16"	1 1/8"	27/32"	2"	HARDENED STEEL
8812	5/16"	1 1/8"	27/32"	2"	STAINLESS STEEL
8813	5/16"	1 1/8"	27/32"	2"	HARDENED STAINLESS STEEL STAINLESS STEEL
8815*	5/16"	1 1/8"	27/32"	2"	HARDENED STAINLESS STEEL BRASS
88X3	5/16"	1 1/2"	27/32"	2"	HARDENED STEEL
88X5*	5/16"	1 1/2"	27/32"	2"	STAINLESS STEEL
8821	5/16"	2"	27/32"	2"	HARDENED STAINLESS STEEL BRASS
8822	5/16"	2"	27/32"	2"	HARDENED STEEL
8823	5/16"	2"	27/32"	2"	STAINLESS STEEL
8825*	5/16"	2"	27/32"	2"	HARDENED STAINLESS STEEL BRASS
8831	5/16"	3"	27/32"	2"	HARDENED STEEL
8832	5/16"	3"	27/32"	2"	STAINLESS STEEL
8833	5/16"	3"	27/32"	2"	HARDENED STEEL
8842	5/16"	4"	27/32"	2"	STAINLESS STEEL

* Meets or exceeds grade 5 of the ASTM F883 standards for cutting.
Key-retaining feature available for all models in this section.

Wilson Bohannon Lock Company

621 Buckeye Street • Marion, OH 43302 • www.padlocks.com
T: 800-382-3639 • F: 740-383-1653 • wbc@padlocks.com