

## Door Key Compatible (Key in Knob) Padlocks

## Series 89 - Model Comparison

	Shackle Measurements			Body Width	
Model	Α	В	С	D	Shackle Material
89T5*	9.53mm	19.05mm	20.64mm	50.8mm	HARDENED STAINLESS STEEL
8911	9.53mm	28.58mm	20.64mm	50.8mm	BRASS
8912	9.53mm	28.58mm	20.64mm	50.8mm	HARDENED STEEL
8913	9.53mm	28.58mm	20.64mm	50.8mm	STAINLESS STEEL
8915*	9.53mm	28.58mm	20.64mm	50.8mm	HARDENED
89X5*	9.53mm	38.1mm	20.64mm	50.8mm	STAINLESS STEEL HARDENED
8921	9.53mm	50.8mm	20.64mm	50.8mm	STAINLESS STEEL BRASS
8922	9.53mm	50.8mm	20.64mm	50.8mm	HARDENED STEEL
8923	9.53mm	50.8mm	20.64mm	50.8mm	STAINLESS STEEL
8925*	9.53mm	50.8mm	20.64mm	50.8mm	HARDENED
8931	9.53mm	76.2mm	20.64mm	50.8mm	STAINLESS STEEL BRASS
8932	9.53mm	76.2mm	20.64mm	50.8mm	HARDENED STEEL
8933	9.53mm	76.2mm	20.64mm	50.8mm	STAINLESS STEEL
8992	9.53mm	127mm	20.64mm	50.8mm	HARDENED STEEL

<sup>\*</sup> Meets or exceeds grade 6 of the ASTM F883 standards for cutting. Key-retaining feature available for all models in this section.

## Wilson Bohannan Lock Company

621 Buckeye Street • Marion, OH 43302 • www.padlocks.com T: 800-382-3639 • F: 740-383-1653 • wbco@padlocks.com