



Door Key Compatible (Key in Knob) Padlocks

Series 89 - Model Comparison

Model	Shackle Measurements			Body Width	Shackle Material
	A	B	C	D	
89T5*	3/8"	3/4"	53/64"	2"	HARDENED STAINLESS STEEL BRASS
8911	3/8"	1 1/8"	53/64"	2"	HARDENED STEEL
8912	3/8"	1 1/8"	53/64"	2"	STAINLESS STEEL
8913	3/8"	1 1/8"	53/64"	2"	HARDENED STAINLESS STEEL HARDENED STAINLESS STEEL BRASS
8915*	3/8"	1 1/8"	53/64"	2"	HARDENED STEEL
89X5*	3/8"	1 1/2"	53/64"	2"	STAINLESS STEEL
8921	3/8"	2"	53/64"	2"	HARDENED STAINLESS STEEL BRASS
8922	3/8"	2"	53/64"	2"	HARDENED STEEL
8923	3/8"	2"	53/64"	2"	STAINLESS STEEL
8925*	3/8"	2"	53/64"	2"	HARDENED STAINLESS STEEL BRASS
8931	3/8"	3"	53/64"	2"	HARDENED STEEL
8932	3/8"	3"	53/64"	2"	STAINLESS STEEL
8933	3/8"	3"	53/64"	2"	HARDENED STEEL
8992	3/8"	5"	53/64"	2"	STAINLESS STEEL

* Meets or exceeds grade 6 of the ASTM F883 standards for cutting.
Key-retaining feature available for all models in this section.

Wilson Bohannon Lock Company

621 Buckeye Street • Marion, OH 43302 • www.padlocks.com
T: 800-382-3639 • F: 740-383-1653 • wbco@padlocks.com