



High Security (Double Ball Locking) Padlocks

Series X - Model Comparison

Model	Shackle Measurements			Body Width	Shackle Material
	A	B	C	D	
XT5*	7.94mm	19.05mm	20.64mm	44.45mm	HARDENED STAINLESS STEEL BRASS
XG1	7.94mm	28.58mm	20.64mm	44.45mm	HARDENED STEEL
XG2	7.94mm	28.58mm	20.64mm	44.45mm	STAINLESS STEEL
XG3	7.94mm	28.58mm	20.64mm	44.45mm	HARDENED STEEL
XG5*	7.94mm	28.58mm	20.64mm	44.45mm	STAINLESS STEEL
X43	7.94mm	38.1mm	20.64mm	44.45mm	HARDENED STAINLESS STEEL STAINLESS STEEL
X45*	7.94mm	38.1mm	20.64mm	44.45mm	HARDENED STAINLESS STEEL BRASS
X61	7.94mm	50.8mm	20.64mm	44.45mm	HARDENED STEEL
X62	7.94mm	50.8mm	20.64mm	44.45mm	STAINLESS STEEL
X63	7.94mm	50.8mm	20.64mm	44.45mm	HARDENED STEEL
X65*	7.94mm	50.8mm	20.64mm	44.45mm	STAINLESS STEEL
X71	7.94mm	76.2mm	20.64mm	44.45mm	HARDENED STAINLESS STEEL BRASS
X72	7.94mm	76.2mm	20.64mm	44.45mm	HARDENED STEEL
X73	7.94mm	76.2mm	20.64mm	44.45mm	STAINLESS STEEL
X82	7.94mm	101.6mm	20.64mm	44.45mm	HARDENED STEEL

* Meets or exceeds grade 5 of the ASTM F883 standards for cutting
Key-retaining feature available for all models in this section.

Wilson Bohannon Lock Company

621 Buckeye Street • Marion, OH 43302 • www.padlocks.com
T: 800-382-3639 • F: 740-383-1653 • wbco@padlocks.com