



## High Security (Double Ball Locking) Padlocks

### Series X - Model Comparison

Model	Shackle Measurements			Body Width	Shackle Material
	A	B	C	D	
XT5*	5/16"	3/4"	27/32"	1 3/4"	HARDENED STAINLESS STEEL
XG1	5/16"	1 1/8"	27/32"	1 3/4"	BRASS
XG2	5/16"	1 1/8"	27/32"	1 3/4"	HARDENED STEEL
XG3	5/16"	1 1/8"	27/32"	1 3/4"	STAINLESS STEEL
XG5*	5/16"	1 1/8"	27/32"	1 3/4"	HARDENED STAINLESS STEEL
X43	5/16"	1 1/2"	27/32"	1 3/4"	STAINLESS STEEL
X45*	5/16"	1 1/2"	27/32"	1 3/4"	HARDENED STAINLESS STEEL
X61	5/16"	2"	27/32"	1 3/4"	BRASS
X62	5/16"	2"	27/32"	1 3/4"	HARDENED STEEL
X63	5/16"	2"	27/32"	1 3/4"	STAINLESS STEEL
X65*	5/16"	2"	27/32"	1 3/4"	HARDENED STAINLESS STEEL
X71	5/16"	3"	27/32"	1 3/4"	BRASS
X72	5/16"	3"	27/32"	1 3/4"	HARDENED STEEL
X73	5/16"	3"	27/32"	1 3/4"	STAINLESS STEEL
X82	5/16"	4"	27/32"	1 3/4"	HARDENED STEEL

\* Meets or exceeds grade 5 of the ASTM F883 standards for cutting  
Key-retaining feature available for all models in this section.

#### Wilson Bohannon Lock Company

621 Buckeye Street • Marion, OH 43302 • [www.padlocks.com](http://www.padlocks.com)  
T: 800-382-3639 • F: 740-383-1653 • [wbco@padlocks.com](mailto:wbco@padlocks.com)